

# Introduction to Neural Computation

---

Prof. Michale Fee  
MIT BCS 9.40 — 2018

Lecture 15  
Perceptrons and Matrix Operations

# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- Two-layer feedforward networks
- Matrix algebra review
- Matrix transformations

# Review


- We have been considering neural networks that use firing rates, rather than spike trains. ('rate model')
- Synaptic input is the firing rate of the input neuron times a synaptic weight  $w$ .

$$I_s = wu$$

- The output firing rate is some non-linear function of the synaptic input.

$$v = F[I_s] = F[wu]$$


input neuron



output neuron

# Review

- We generalized this model to the case when there are many synaptic inputs...



$$I_s = w_1 u_1 + w_2 u_2 + w_3 u_3 + \dots = \sum_b w_b u_b = \vec{w} \cdot \vec{u}$$

$$v = F[\vec{w} \cdot \vec{u}]$$

# Review


- The output firing rate is some non-linear function of the synaptic input.

$$v = F[I_s] = F[wu]$$


input neuron




output neuron



linear neuron




Linear threshold neuron



Binary threshold neuron

# How to build a receptive field

- We can see that the choice of weights allows us to specify the receptive field of our output neuron




$$\vec{w} = [0, -1, 2, -1, 0]$$

# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- Two-layer feedforward networks
- Matrix algebra review
- Matrix transformations



# Perceptrons

- A perceptron carries out classification of inputs that represent features.




# Perceptrons

- A perceptron carries out classification of inputs that represent features.



Binary Threshold Neuron for decision-making




$$v = F(\vec{w} \cdot \vec{u} - \theta)$$

# Classification in two dimensions

$v = F(\vec{w} \cdot \vec{u} - \theta)$       The decision boundary is  $\vec{w} \cdot \vec{u} = \theta$

- Let's calculate the weight vector  $\vec{w} = (w_1, w_2)$  that gives us the decision boundary shown below. Assume  $\theta = 1$ .



We have two points on the decision boundary we know, and two unknowns...

$$\vec{u}_a = (a, 0) \quad \vec{u}_a \cdot \vec{w} = \theta$$

$$\vec{u}_b = (0, b) \quad \vec{u}_b \cdot \vec{w} = \theta$$

$$\vec{w} = (1/a, 1/b)$$

- This is easy to do (by eye!) in two dimensions – but how about in higher dimensions?


# Classification in higher dimensions

- Let's say we have  $n$  observations of our inputs

$$\vec{u} = \vec{\xi}_i, \quad i = 1, 2, \dots, n$$

- After each observation, we are told whether this input corresponds to a dog.

$$T_i = \begin{cases} 1 & \text{for yes} \\ 0 & \text{for no} \end{cases}, \quad i = 1, 2, \dots, n$$



- We want to find  $\vec{w}$ , such that



$$v_i = \text{step}(\vec{w} \cdot \vec{\xi}_i - \theta) = T_i, \quad \text{for all } i$$

# Perceptron learning

- How would we find the weight vector  $w$  that separates dogs from non-dogs?
- Each observation  $\vec{u}_i, T_i$  gives us information we can use to construct  $\vec{w}$ . This is called supervised learning.
- We can learn  $w$  iteratively: i.e., on each observation we will update our estimate of  $\vec{w}$

$$\vec{w} \rightarrow \vec{w} + \Delta\vec{w} \quad \text{Rosenblatt, 1957}$$

- How do we start?
  - we can start with a random set of weights
  - or start with zero weights  $\vec{w} = 0$





# Perceptron learning rule

- On each observation of  $\vec{u} = \vec{\xi}_i$ , we use our current estimate of  $\vec{w}$  to classify  $\vec{\xi}_i$ :

$$v_i = \text{step}(\vec{w} \cdot \vec{\xi}_i - \theta)$$

- Compare our classification to the right answer...
  - If  $v_i = T_i$  then we were right!  
so don't do anything:  $\Delta\vec{w} = 0$






# Perceptron learning rule

- If  $v_i \neq T_i$  then we were wrong, so update  $\vec{w}$ .

$$\Delta \vec{w} = \begin{cases} \eta \vec{\xi}_i, & \text{if } T = 1 \\ -\eta \vec{\xi}_i, & \text{if } T = 0 \end{cases} \quad \eta \text{ is the 'learning rate'}$$

Increase  $w$  in the direction of  $\vec{\xi}_i$  if the correct answer was 1,  
away from  $\vec{\xi}_i$  if the correct answer was 0.




# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- **Neuronal logic, linear separability, and invariance**
- Two-layer feedforward networks
- Matrix algebra review
- Matrix transformations

# Neuronal Logic



- The perceptron naturally implements simple logic gates...



OR

$$\vec{w} = (1, 1)$$


$$\theta = 0.5$$



AND


$$\vec{w} = (1, 1)$$

$$\theta = 1.5$$




# Linear separability

- There are some classification problems the perceptron cannot solve.
- Exclusive OR (XOR) – A or B but not both



- The problem of linear separability

Multi-layer perceptron



# Linear separability

- Classification problems are difficult because of transformations such as translation, rotation, scale
- In high dimensional space, images that are related by invariant transformations can be thought of as existing on 'manifolds'

Usually not linearly separable







Figure source unknown. All rights reserved. This content is excluded from our Creative Commons license. For more information, see <https://ocw.mit.edu/help/faq-fair-use/>.

# Invariance

- Multilayer perceptrons can sometimes solve the problem!
- We can break the classification into several linearly separable problems



Multi-layer perceptron



# Deep neural networks

- Multilayer perceptrons can sometimes solve the problem!


Figure removed due to copyright restrictions. See Lecture 15 video or Figure 1 in Yamins, D.L.K., J.J. DiCarlo. "[Using Goal-driven Deep Learning Models to Understand Sensory Cortex.](#)" *Nature Neuroscience* 19 (2016): 356-365.

# Learning Objectives for Lecture 15


- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- **Two-layer feedforward networks**
- Matrix algebra review
- Matrix transformations

# More complex networks

- We have considered increasingly complex network models



input firing rates  $\left[ u_1, u_2, u_3, \dots, u_{n_b} \right] = \vec{u}$



$$I_s = wu$$

$$v = F[wu]$$

$$I_s = \sum_b w_b u_b = \vec{w} \cdot \vec{u}$$

$$v = F[\vec{w} \cdot \vec{u}]$$

# Two-layer feed-forward network


- We can expand our set of output neurons to make a more general network...

input firing rates

$$\begin{bmatrix} u_1, u_2, u_3, \dots, u_{n_b} \end{bmatrix} = \vec{u}$$

output firing rates

$$\begin{bmatrix} v_1, v_2, v_3, \dots, v_{n_a} \end{bmatrix} = \vec{v}$$




# Two-layer feed-forward network

- We can write down the firing rates of our output neurons as follows:

$$v_1 = \vec{w}_{a=1} \cdot \vec{u} \quad v_1 = \sum_b W_{1b} u_b$$

$$v_2 = \vec{w}_{a=2} \cdot \vec{u} \quad v_2 = \sum_b W_{2b} u_b$$

$$v_3 = \vec{w}_{a=3} \cdot \vec{u} \quad v_3 = \sum_b W_{3b} u_b$$




$$\vec{v} = W \vec{u}$$

$$v_a = \vec{w}_a \cdot \vec{u} \quad v_a = \sum_b W_{ab} u_b$$

- Our feed-forward network implements matrix multiplication!

# Two-layer feed-forward network

- We have a weight from each of our input neurons onto each of our output neurons.
- We write the weights as a matrix.




weight matrix

$$W_{ab} = \begin{matrix} & \begin{matrix} b = 1 & 2 & 3 & 4 \end{matrix} \\ \begin{matrix} a = 1 \\ 2 \\ 3 \\ 4 \end{matrix} & \begin{bmatrix} w_{11} & w_{12} & w_{13} & w_{14} \\ w_{21} & w_{22} & w_{23} & w_{24} \\ w_{31} & w_{32} & w_{33} & w_{34} \\ w_{41} & w_{42} & w_{43} & w_{44} \end{bmatrix} \end{matrix} = \begin{bmatrix} \vec{w}_{a=1} \\ \vec{w}_{a=2} \\ \vec{w}_{a=3} \\ \vec{w}_{a=4} \end{bmatrix}$$

# Two-layer feed-forward network

- We can write down the firing rates of our output neurons as a matrix multiplication.

$$\vec{v} = W \vec{u} \quad v_a = \sum_b W_{ab} u_b$$



$$\vec{v} = \begin{bmatrix} v_1 \\ v_2 \\ v_3 \end{bmatrix} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix} \begin{bmatrix} u_1 \\ u_2 \\ u_3 \end{bmatrix} = \begin{bmatrix} \vec{w}_{a=1} \cdot \vec{u} \\ \vec{w}_{a=2} \cdot \vec{u} \\ \vec{w}_{a=3} \cdot \vec{u} \end{bmatrix}$$

- Dot product interpretation of matrix multiplication

# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- Two-layer feedforward networks
- **Matrix algebra review**
- Matrix transformations

# Matrix algebra

- Vectors are collections of numbers.

Let's say we make measurements of two different things,  $x_a$  and  $x_b$ , at a particular time.

$$\vec{x} = \begin{pmatrix} x_a \\ x_b \end{pmatrix}$$

- Matrices are collections of vectors

Now we measure  $x_a$  and  $x_b$  at three different times

$$\vec{x}_1 = \begin{pmatrix} 1 \\ 3 \end{pmatrix} \quad \vec{x}_2 = \begin{pmatrix} -2 \\ 4 \end{pmatrix} \quad \vec{x}_3 = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

We can write all our measurements down as a matrix

$$X = (\vec{x}_1 | \vec{x}_2 | \vec{x}_3) = \begin{pmatrix} 1 & -2 & 0 \\ 3 & 4 & 1 \end{pmatrix}$$

```
x1=[1;3]      %column  
x2=[-2;4]    %column  
x3=[0;1]     %column  
X=[x1,x2,x3] %concatenate
```

# Matrix algebra

- Labeling matrix elements

$$\mathbf{X} = \begin{pmatrix} x_{11} & x_{12} & x_{13} \\ x_{21} & x_{22} & x_{23} \end{pmatrix} \quad \text{2 rows x 3 columns}$$

- Matrix transpose flips the rows and columns

$$\mathbf{X}^T = \begin{pmatrix} x_{11} & x_{21} \\ x_{12} & x_{22} \\ x_{13} & x_{23} \end{pmatrix} \quad \text{3 rows x 2 columns}$$

- Symmetric matrix

$$\mathbf{X} = \begin{pmatrix} a & c \\ c & b \end{pmatrix} \quad \mathbf{X}^T = \mathbf{X}$$

# Matrix multiplication

- In general, we carry out matrix multiplication by taking dot products of all the rows of the first matrix with all the columns of the second matrix.

$$A = \begin{pmatrix} 1 & -2 & 0 \\ 3 & 4 & 1 \end{pmatrix} \quad B = \begin{pmatrix} 4 & 2 \\ 7 & 3 \\ -1 & 0 \end{pmatrix}$$

$$AB = \begin{pmatrix} 1 & -2 & 0 \\ 3 & 4 & 1 \end{pmatrix} \begin{pmatrix} 4 & 2 \\ 7 & 3 \\ -1 & 0 \end{pmatrix} = \begin{pmatrix} -10 & -4 \\ 39 & 18 \end{pmatrix}$$

$m \times k$                    $k \times n$                                    $m \times n$

$$\begin{pmatrix} 4 - 14 + 0 & 2 - 6 + 0 \\ 12 + 28 - 1 & 6 + 12 + 0 \end{pmatrix}$$

$$AB \neq BA$$

# Matrix algebra

- We can still do all our vector operations on the vectors in  $X$
- For example, let's take the dot product of each of our vectors  $\vec{x}_1, \vec{x}_2, \vec{x}_3$  with another vector  $\vec{v}$ .  $\vec{v} = \begin{pmatrix} 1 \\ -1 \end{pmatrix}$

- We can do this in two different ways:

$$\vec{y} = \vec{v}^T X = \begin{pmatrix} 1 & -1 \end{pmatrix} \begin{pmatrix} 1 & -2 & 0 \\ 3 & 4 & 1 \end{pmatrix} = \begin{pmatrix} -2 & -6 & -1 \end{pmatrix}$$

$1 \times 2 \qquad \qquad 2 \times 3 \qquad \qquad 1 \times 3$

# Matrix algebra

- Alternatively, let's take the dot product of each of our vectors  $\vec{x}_1, \vec{x}_2, \vec{x}_3$  with another vector  $\vec{v}$ .
- We can do it like this...

$$\vec{y} = X^T \vec{v} = \begin{pmatrix} 1 & 3 \\ -2 & 4 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 \\ -1 \end{pmatrix} = \begin{pmatrix} -2 \\ -6 \\ -1 \end{pmatrix}$$

`v=[1;-1] %column`  
`y=X'*v %' is transpose`

- Note that matrix multiplication takes the dot product of each of the rows of the first matrix with each of the columns of the second matrix!

# Identity matrix

- When multiplying numbers, the number 1 has a special property:

$$a \cdot 1 = a$$

- Is there a matrix that when multiplied by A yields A?

$$AI = A$$

- Yes! It is called the 'Identity Matrix'  $I = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$

$$I \vec{x} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \vec{x}$$

# Systems of equations

- Square matrices are very useful
- How do we solve this simple equation?    divide both sides by  $a$

$$ax = c$$

$$x = a^{-1}c$$

- Now let's consider a 'system' of equations

$$x - 2y = 3$$

$$3x + y = 5$$

$$A\vec{x} = \vec{c}$$

where

$$A = \begin{pmatrix} 1 & -2 \\ 3 & 1 \end{pmatrix}$$

$$\vec{c} = \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$

- We can write this as:

$$\begin{pmatrix} 1 & -2 \\ 3 & 1 \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} = \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$

# Systems of equations

- How do we divide both sides by  $A$ ?  $A\vec{x} = \vec{c}$
- We can't, but we can multiply both sides by something which makes the  $A$  go away!
- The matrix inverse of  $A$ , denoted  $A^{-1}$ , has the property that:

$$A^{-1}A = I$$

- Thus to solve the system of equations  $A\vec{x} = \vec{c}$ 
  - Multiply both sides of the eqn by  $A^{-1}$

$$\underbrace{A^{-1}A}_{I} \vec{x} = A^{-1}\vec{c}$$

$$I \vec{x} = A^{-1}\vec{c}$$



$$\vec{x} = A^{-1}\vec{c}$$

# Matrix inverse in 2d

- For a matrix  $A$  given by  $A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$

the inverse of  $A$  is given by

$$A^{-1} = \frac{1}{\det(A)} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$$

where the determinant is given by:

$$\det(A) = ad - bc$$

$$A^{-1}A = \frac{1}{\det(A)} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix} \begin{pmatrix} a & b \\ c & d \end{pmatrix}$$

$$= \frac{1}{\det(A)} \begin{pmatrix} ad - bc & db - bd \\ -ca + ac & -cb + ad \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

The matrix has an inverse iff  $\det(A) \neq 0$

The matrix is 'singular' if  $\det(A) = 0$

# Matrix inverse in 2d

- Back to our system of equations

$$A\vec{x} = \vec{c} \quad A = \begin{pmatrix} 1 & -2 \\ 3 & 1 \end{pmatrix} \quad \vec{c} = \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$

- The determinant is  $\det(A) = 1 - (-6) = 7$  so there is an inverse.

$$A^{-1} = \frac{1}{7} \begin{pmatrix} 1 & 2 \\ -3 & 1 \end{pmatrix}$$

- Thus,

$$\vec{x} = A^{-1}\vec{c} = \frac{1}{7} \begin{pmatrix} 1 & 2 \\ -3 & 1 \end{pmatrix} \begin{pmatrix} 3 \\ 5 \end{pmatrix} = \frac{1}{7} \begin{pmatrix} 13 \\ -4 \end{pmatrix}$$

# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- Two-layer feedforward networks
- Matrix algebra review
- **Matrix transformations**

# Matrix transformation

- You can see from our system of equations that the matrix A 'transformed' vector x into the vector c


$$\vec{x} = \begin{pmatrix} 13/7 \\ -4/7 \end{pmatrix} \quad \vec{c} = A\vec{x} \quad \vec{c} = \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$


- The matrix  $A^{-1}$  transformed vector c back into the vector x

$$\vec{x} = \begin{pmatrix} 13/7 \\ -4/7 \end{pmatrix} \quad \vec{x} = A^{-1}\vec{c} \quad \vec{c} = \begin{pmatrix} 3 \\ 5 \end{pmatrix}$$


# Matrix transformation

- In general  $A$  maps the set of vectors in  $\mathbb{R}^2$  onto another set of vectors in  $\mathbb{R}^2$ . What do these mappings look like?



# Matrix transformation



- We already know the simplest transformation, when  $A = \text{identity}$

$$\vec{y} = I \vec{x} = \vec{x}$$

It is instructive to consider small perturbations from the identity matrix.

$$\vec{y} = A \vec{x} \quad A = I + \Delta = \begin{pmatrix} 1 + \delta & 0 \\ 0 & 1 + \delta \end{pmatrix}$$

```
x=randn(2,N1); % Gaussian  
delta=0.3;  
I=[1,0;0,1];  
A=I+[delta,0;0,delta];  
y=A*x;
```




# Matrix transformation

- It is instructive to consider small perturbations from the identity matrix. For example...  $\vec{y} = A\vec{x}$


Stretch in x-direction

$$A = \begin{pmatrix} 1 + \delta & 0 \\ 0 & 1 \end{pmatrix}$$



Stretch in y-direction


$$A = \begin{pmatrix} 1 & 0 \\ 0 & 1 + \delta \end{pmatrix}$$



# Matrix transformation

- It is instructive to consider small perturbations from the identity matrix. For example...  $\vec{y} = A\vec{x}$

$$A = \begin{pmatrix} 1 + \delta & 0 \\ 0 & 1 - \delta \end{pmatrix}$$




# Matrix symmetries

- Matrix multiplication can be used to produce 'symmetry operations'


Mirror reflection

$$A = \begin{pmatrix} -1 & 0 \\ 0 & 1 \end{pmatrix}$$



Inversion through the origin

$$A = \begin{pmatrix} -1 & 0 \\ 0 & -1 \end{pmatrix}$$




# Matrix transformations


$$\vec{y} = A\vec{x}$$

- Perturbations from the identity matrix


$$A = \begin{pmatrix} 1+\delta & 0 \\ 0 & 1+\delta \end{pmatrix}$$




$$A = \begin{pmatrix} 1+\delta & 0 \\ 0 & 1 \end{pmatrix}$$




$$A = \begin{pmatrix} 1 & 0 \\ 0 & 1+\delta \end{pmatrix}$$




$$A = \begin{pmatrix} 1+\delta & 0 \\ 0 & 1-\delta \end{pmatrix}$$



$$A = \begin{pmatrix} -1 & 0 \\ 0 & 1 \end{pmatrix}$$



$$A = \begin{pmatrix} -1 & 0 \\ 0 & -1 \end{pmatrix}$$



These are all diagonal matrices

$$\Lambda = \begin{pmatrix} a & 0 \\ 0 & b \end{pmatrix}$$


$$\Lambda^{-1} = \begin{pmatrix} a^{-1} & 0 \\ 0 & b^{-1} \end{pmatrix}$$

# Matrix transformation

- It is instructive to consider small perturbations from the identity matrix.


Shear along x

$$A = \begin{pmatrix} 1 & +\delta \\ 0 & 1 \end{pmatrix}$$



Shear along y

$$A = \begin{pmatrix} 1 & 0 \\ -\delta & 1 \end{pmatrix}$$




# Matrix transformation

- It is instructive to consider small perturbations from the identity matrix.

Rotation!

$$A = \begin{pmatrix} 1 & +\delta \\ -\delta & 1 \end{pmatrix}$$




# Rotation matrix

- We can implement a rotation in the plane by an arbitrary angle  $\theta$  with the following matrix.


$$\Phi(\theta) = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$$

$$\Phi(45^\circ) = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & -1 \\ 1 & 1 \end{pmatrix}$$


$\theta = 10^\circ$




$\theta = 25^\circ$



$\theta = 45^\circ$



$\theta = 90^\circ$



# Rotation matrix

- Does a rotation matrix have an inverse?  $\det(\Phi) = 1$

$$\Phi(\theta) = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix} \quad \Phi(-\theta) = \begin{pmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{pmatrix}$$


- A rotation by angle  $+\theta$  followed by a rotation by angle  $-\theta$  just puts everything back where it was.

$$\Phi(-\theta)\Phi(\theta) = I \quad \Phi^{-1}(\theta) = \Phi(-\theta)$$

- Also, the inverse of A is just the transpose of A!

$$\Phi^{-1}(\theta) = \Phi^T(\theta)$$

# Two-layer feed-forward network



- Our feed-forward network implements an arbitrary matrix transformation!

$$\vec{v} = W \vec{u}$$


# Learning Objectives for Lecture 15

- Perceptrons and perceptron learning rule
- Neuronal logic, linear separability, and invariance
- Two-layer feedforward networks
- Matrix algebra review
- Matrix transformations

# Rotated transformations

- The rotation matrix allows us to do a very cool trick.
- We can do any of the transformations above (stretch, mirror reflection, shear), not just along the axes, but in any arbitrary direction.

For example, stretch along a  $45^\circ$  angle



# Rotated transformations

- We will do this by making three successive transformations:

'Unrotate' our vectors by angle  $-\theta$ :  $\Phi(-\theta) = \Phi^T(\theta)$

Make a transformation:  $\Lambda$

Then rotate our vectors back by angle  $\theta$ :  $\Phi(\theta)$


- We do each of these steps by multiplying our matrices together

$$\Phi \Lambda \Phi^T \vec{x}$$

# Rotated transformations

- Let's construct a matrix that produces a stretch along a 45° angle...


$\vec{x}$




$\Phi^T \vec{x}$



$\Lambda \Phi^T \vec{x}$



$\Phi \Lambda \Phi^T \vec{x}$



$$\Phi^T = \Phi(-45^\circ)$$

$$= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ -1 & 1 \end{pmatrix}$$

$\Lambda$

$$= \begin{pmatrix} 2 & 0 \\ 0 & 1 \end{pmatrix}$$

$\Phi(+45^\circ)$

$$= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & -1 \\ 1 & 1 \end{pmatrix}$$

$$\Phi \Lambda \Phi^T = \frac{1}{2} \begin{pmatrix} 3 & 1 \\ 1 & 3 \end{pmatrix}$$

MIT OpenCourseWare  
<https://ocw.mit.edu/>

9.40 Introduction to Neural Computation  
Spring 2018

For information about citing these materials or our Terms of Use, visit: <https://ocw.mit.edu/terms>.